

Model	DA1215-H1	DA1815-H2	DA2415-H2
Power supply (V/hz)	115/60	208-230/60	208-230/60
Cooling	12,000	18,000	22,000
Heating	12,000	18,000	22,000
SEER	15	15	15
HSPF	8.2	8.2	8.2
EER	9	9	9
Dehumidification (Pts/hr)	2.75	3.8	5.3
Current (A) Cooling	11.9	8.7	10.6
Heating	11.7	8	9.7
Power Input (W) Cooling	1340	1920	2340
Heating	1320	1750	2150
Indoor Air Circulation L / M / H (CFM)	240/290/340	280/390/440	560/680/740
Indoor Noise level dB(A): L / M / H	29/35/39	31/39/42	39/45/49
Outdoor Noise Level dB(A)	~ 55	~ 55	~ 55
Indoor Dimensions W x D x H (In.)	30.3 X 7.4 X 10.0	35.6 X 7.8 X 10.8	40.6 X 8.6 X 12.4
Indoor Package Dimensions W x D x H (In.)	32.9 X 10.4 X 13.0	38.2 X 10.6 X 13.6	43.9 X 15.6 X 11.8
Indoor Net Weight (lbs.)	16.5	19.8	26.5
Indoor Gross Weight (lbs.)	21	25.4	33.1
Outdoor Dimensions W x D x H (In.)	26.0 X 10.4 X 21.3	29.9 X 11.2 X 23.2	33.3 X 12.6 X 27.6
Outdoor Package Dimensions W x D x H (In.)	31.1 X 14.0 X 24.4	34.9 X 14.0 X 25.4	38.0 X 15.6 X 29.7
Outdoor Net Weight (lbs.)	66.1	82.7	103.6
Outdoor Gross Weight (lbs.)	70.6	88.2	111.3
Refrigerant	R410A	R410A	R410A